







PORT LIGHT

FOR MOTOR YACHT AND SAILING VESSEL UP TO 50mt

VISIBILITY [NM]: >3 POWER [W]: 8

Possibility to be combined

Accessories on page 52

TECHNICAL FEATURES

Dimensions Operating voltage	Ø: 110mm h: 75mm 24 VDC (Range of operating voltage: 18÷32 VDC)
Current on leds Overcurrent protection Protection level	Constant in the range of Operating Voltage >2A IP68
Materials available	Aluminum : anodized ANTICORODAL 6082 Steel : passivated and polished stainless steel AISI 316L
Optical window	Transparent Borosilicate Glass

ORDER CODE








ALUMINIUM BLACK code: CE NL S 04 BA **STAINLESS STEEL** code: CE NL S 04 SS



DECK BRACKET


WHITE ALU	CE NL DB GA
BLACK ALU	CE NL DB BA
S.STEEL	CE NL DB SS



Dimensions (mm): 110

SIDE BRACKET

WHITE ALU	CE NL SB GA
BLACK ALU	CE NL SB BA
S.STEEL	CE NL SB SS



Dimensions (mm): 110

ROUND BRACKET

WHITE ALU	CE NL DB 2G GA
BLACK ALU	CE NL DB 2G BA
S.STEEL	CE NL DB 2G SS

Dimensions (mm): 110

